

(19) World Intellectual Property  
Organization  
International Bureau




(43) International Publication Date  
21 May 2004 (21.05.2004)

PCT

(10) International Publication Number  
WO 2004/042161 A1

- (51) International Patent Classification<sup>7</sup>: E04B 5/40, E04C 3/293, 3/294, 5/06
- (21) International Application Number: PCT/AU2003/001452
- (22) International Filing Date: 4 November 2003 (04.11.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 2002952445 4 November 2002 (04.11.2002) AU
- (71) Applicants (for all designated States except US): ONES-TEEL REINFORCING PTY LTD [AU/AU]; Level 23, 1 York Street, Sydney, New South Wales 2000 (AU). UNIVERSITY OF WESTERN SYDNEY [AU/AU]; Second Avenue, Kingswood, New South Wales 2747 (AU).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): PATRICK, Mark [AU/AU]; 32 Lewin Street, Springwood, New South Wales 2777 (AU).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (regional): ARIPO patent (BW, GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: A COMPOSITE BEAM



(57) Abstract: A composite beam is disclosed. The beam includes an internal horizontal beam (5), a composite slab that is positioned on and supported by the beam, and a plurality of shear connectors (15), embedded in the cast concrete and welded to the beam and connecting the composite slab to the beam. The beam is characterised by a reinforcing component (19) that is positioned so that reinforcing elements (61, 63) of the reinforcing component intersect a conical-type failure surface around the shear connectors in at least two different, preferably perpendicular, directions.